



## Master-Tube PA Brake

Special polyamide hose for brake and automotive applications



spiral-free



metal-free

### Product Details

#### Construction / Material

- Type of construction: axially extruded tubing without seams or welds
- Execution of the wall: made of highly abrasion-resistant material / dimensions and tolerances correspond to DIN 73378 and manufactured according to DIN 74324

#### Properties

- Specifications of the product: manufactured with calibrated outer diameter
- Chemical Properties: good resistance to chemicals / good resistance to oil / good UV resistance / halogen-free / hydrolysis resistant / free from paint wetting impairment substances (LABS)
- Mechanical Properties: small bending radius / material is resistant to stress corrosion cracking / high mechanical strength and impact resistance
- Colour: black

#### Operating Temperature

- Temperature Range: -40 to 90 °C

#### Delivery Information

- Delivery, type of production: inner diameter: 2.0 - 16.0 mm / outer diameter: 4.0 - 20.0 mm

#### Application Areas

- Areas of application: Automotive / Plant & Mechanical Engineering / Industry / Sea & Rail transport / Cable manufacturers / Vehicle Construction

### Customizing Options

- optional item modification (on request): printable / rolls

## Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

## Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

### Individual consultation

We offer consultation by  
phone:  
+49 209 97077-112

Product requests via  
[masterflex.de/en](https://masterflex.de/en)

### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

