

Master-Tube PUR A

PU tubing, various hardnesses, available as polyurethane ester and ether, anti-static version, abrasion-resistant, UV-resistant

antistatic spiral-free metal-free

Product Details

Construction / Material

- Type of construction: axially extruded tubing without seams or welds
- Execution of the wall: made of highly abrasion-resistant material
- Specifications of the wall: surface resistance $R_o < 10^8$ Ohm

Properties

- Chemical Properties: good resistance to oil, plasticiser-free, good resistance to fats
- Mechanical Properties: kink-resistant
- Physical Properties: good damping behaviour

Operating Temperature

- Temperature Range: -40 to 85 °C

Application Areas

- Areas of application: Plant & Mechanical Engineering, Industry

Customizing Options

- optional item modification (on request): printable, rolls

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).



Individual consultation

We offer consultation by phone: **+44 161 626 8066**

Product requests via: **https://www.masterflex-hose.co.uk/**

Headquarters for your sales area

Masterflex Technical Hoses, Ltd.

Units G & H
Prince of Wales Business Park
Vulcan Street
Oldham OL1 4ER
Great Britain