




Master-Tube PUR

Polyurethane hoses: Used, among other things, as paint and varnish hoses (colour: white), as water cooling hoses (colour: transparent or coloured); for guiding special cables (colour: blue or other colours) and as drag chain-compatible hoses (colour: black).



spiral-free



metal-free



flexible

Product Details

Construction / Material

- Execution of the wall: made of highly abrasion-resistant material

Properties

- Chemical Properties: good resistance to oil, good UV resistance, plasticiser-free, good resistance to fats
- Mechanical Properties: kink-resistant, elastic behaviour under mechanical stress
- Flexibility: flexible
- Physical Properties: flexible at low temperatures, good damping behaviour

Operating Temperature

- Temperature Range: -40 to 90 °C

Application Areas

- Areas of application: Plant & Mechanical Engineering, Industry

Customizing Options

- optional item modification (on request): other colours, printable, rolls, available in antistatic design, manufactured from hydrolysis- and microbe-resistant special PUR materials

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).



Individual consultation

We offer consultation by phone: **+44 161 626 8066**

Product requests via: <https://www.masterflex-hose.co.uk/>

Headquarters for your sales area

Masterflex Technical Hoses, Ltd.

Units G & H
Prince of Wales Business Park
Vulcan Street
Oldham OL1 4ER
Great Britain