



## Combiflex PU Hose Connector

screw-on PU hose connector for Master-PUR L and H hoses

---

### Product Details

#### Construction / Material

- Specification of the connection solution: tension-resistant and largely leak-proof connection
- Design of the hose connector: high mechanical strength and impact resistance / made of abrasion resistant material
- Material of the hose connector: polyurethane

#### Properties

- Chemical Properties: hydrolysis resistant / microbe-resistant
- Colour: black
- Other: reusable and replaceable / easy to assemble

#### Operating Temperature

- Temperature Range: -40 to 90 °C
- short-term maximum temperature: peaks to 125 °C

#### Delivery Information

- Delivery, type of production: various nominal widths are available ex production, individual nominal widths also ex stock

#### Application Areas

#### Customizing Options

---

### Article Variants

Article number	DN of the hose mm	Piece weight kg	Length (h1) mm
002020	25	0.09	65
002021	32	0.10	70
002022	38	0.13	75
002023	50	0.20	90
002025	65	0.23	100
002028	80	0.39	115
002029	100	0.58	125

Subject to technical changes and colour deviations

## Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

## Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

### Individual consultation

We offer consultation by  
phone:  
+49 209 97077-112

Product requests via  
[masterflex.de/en](https://www.masterflex.de/en)

### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

