



Cuff for Master-VAC

Special sleeve for connection of Master-VAC hoses, electrically conductive

Product Details

Construction / Material

- design of the cuff: made of electrically conductive material
- material of the cuff: Polyethylene
- material specification of the cuff: surface resistance $R_0 < 10^6 \text{ Ohm}$

Properties

- Chemical Properties: odourless and tasteless / good resistance to chemicals / stainless
- Other: easy to assemble

Operating Temperature

- Temperature Range: 0 to 70 °C

Delivery Information

- Delivery, type of production: available from stock in the stated nominal widths in black

Application Areas

Customizing Options

- optional item modification (on request): other nominal widths

Article Variants

Article number	DN of the hose mm	Outer Ø of the pipe (d1) mm	Clamping range outside (d3) mm	Outer Ø of the sprue on the hose side (d3) mm	Screw-in depth of the hose mm	Insertion depth of the threaded socket mm	Piece weight kg	Length mm
----------------	-------------------	-----------------------------	--------------------------------	---	-------------------------------	---	-----------------	-----------

002531	32	32	37.5 - 38.5	44.5	38	55.5	0.035	93.5
002532	38	38	44.5 - 45.75	52	38	55.5	0.046	93.5
002533	45	45	50 - 51	58.5	38	55.5	0.049	93.5
002534	50	50	57 - 58.5	66	38	55.5	0.059	93.5

Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

Individual consultation

We offer consultation by phone:
+49 209 97077-112

Product requests via
[masterflex.de/en](https://www.masterflex.de/en)

Address Headquarters

Masterflex SE
Willy-Brandt-Allee 300
45981 Gelsenkirchen

